

Load Data



Cartridge

357 MAG

Projectile (SKU)

357ARX357-86

Bullet Type

ARX

Test Barrel Length (Inches)

10.00"

Twist Rate

1:18.75

BC / SD

.048 / .096

Bullet Length

.711"

Bullet Diameter

.357"

Bullet Weight

86 Grains

Cartridge Overall Length (Inches)

1.570"

Case

Jagemann

Trim Length (In)

1.278"

Primer Type

Small Pistol

Starting Load

Powder	Charge (Grains)	Velocity (FPS)	Pressure (PSI)
Lovex D036-03	8.0	1,461	20,460
Hodgdon HS-6	8.2	1,486	20,130
Hodgdon HP-38	6.0	1,424	21,960

Maximum Load

Charge (Grains)	Velocity (FPS)	Pressure (PSI)
10.0	1,803	33,070
10.0	1,815	33,270
7.5	1,715	33,940

WARNINGS

This guide is intended to be used as a reference. Each individual must determine what is the best and safest load for their firearm. The loads detailed in this guide were generated at the ballistics test facility of Inceptor Ammunition, in accordance with SAAMI (Sporting Arms and Ammunition Manufacturer's Institute) guidelines. All loads are fired through test barrels and individual results fired through different firearms may vary. The reloader is cautioned to read and follow safe reloading practices such as those outlined in standard reloading manuals before attempting to reload any cartridge. These projectiles are sensitive to over crimping. These projectiles are sensitive to over crimping.

DISCLAIMER

Inceptor Ammunition has developed this guide to provide reloaders with recommended loads for this particular projectile. Inceptor has no control over the actual reloading procedures used and condition or choice of firearms and components used. No responsibility for the use of this data is implied or assumed. The buyer/user assumes full responsibility, risk, and liabilities for all injuries (including death), damages, and/or losses to persons or properties resulting from the use/misuse of these products. The ballistics data contained in this guide was obtained at Inceptor Ammunition's ballistics facilities under strictly controlled conditions and is applicable ONLY for the powders listed. It is important to remember that equipment variations and different reloading techniques, as well as component variations, will most likely yield slightly different ballistics data. With this in mind, it is imperative that you do not exceed the maximum charge recommendations and that you always start loading with the minimum powder charges in the loads described.